



# GOVERNMENT COLLEGE UNIVERSITY FAISALABAD

## **TENDER DOCUMENT No. 392/2017**

### **SUPPLY OF EQUIPMENTS FOR DEPARTMENT OF PHARMACEUTICS, GCUF.**

**Purchase Price: Rs. 500/-**

**Sealed Tenders are invited from the well reputed firms / suppliers, who are registered with Sales Tax and Income Tax Departments as Active Tax Payer for Supply of Equipments for Department of Pharmaceutics, GCUF.**

#### **GENERAL TERMS & CONDITIONS**

**1. Tender Opening Date & Procedure:**

The procurement shall be completed in accordance with Punjab Procurement Rules 2014, on Single Stage – Two Envelope Bidding Procedure.

Bids in complete conformity with Tender Documents will be dropped in Tender Box placed at Procurement Department of the GCUF, not later than **10:00 Hrs on 30.03.2017** which shall be opened on same day at **10:30 Hours**.

**Note: Tender Number must be mentioned on envelope.**

**2. Tender Fee, Bid Security and Performance Security:**

The Bid must be accompanied by Tender Fee of Rs:500/- in shape of Call Deposit Receipt (CDR) in original and Bid Security of 2% of Estimated Price of Rs.1,283,000/- (refundable) in shape of Call Deposit Receipt (CDR) in original.

CDRs must be in favor of Treasurer, Government College University, Faisalabad. The rates / bids should be inclusive of all applicable Govt. Taxes.

**3. Validity of Offers.**

- i. Offers shall be valid for 180 days from the date of submission of bids.
- ii. Withdrawal / modification of the original offer within the validity period shall entitle the University to forfeit Bid Security.
- iii. Sales Tax Number and NTN Number must be mentioned on the letter head and bidding documents.

**4. Failures and Terminations:**

No offer of a supplier / firm will be considered if:-

- a) Bid received without Bid Security / Call Deposit or less CDR than the required.
- b) Bids received not in accordance with Tender Documents and Tender Notice.
- c) Bid received later than the date and time fixed for tender.
- d) Tender is incomplete in any respect or is unsigned.
- e) Offer is ambiguous and the offer is conditional.
- f) Offer from a firm which is black listed at any level.
- g) Any erasing / cutting / overwriting etc.
- h) The supplier fails to deliver the consignment within specified delivery period strictly in accordance with the terms and conditions as laid down in the Purchase Order.
- i) Situation warranted, then University is authorized to forfeit the bid Security and the firm may also be black listed.

**5. Other special conditions**

- I. The decision of the Vice Chancellor of Government College University, Faisalabad, would be final & binding on both the parties.
- II. 10% performance security shall be deducted from the final bill of the successful bidder as per PPRA Rules 2014. (if applicable)
- III. All Government Taxes will be deducted according to applicable rules.
- IV. The University may reject all bids/proposals at any time prior to the acceptance of a bid or proposal as per PPRA Punjab rule 35, however upon bidder request the ground of rejection will be communicated to the concerned but no justification will be given as per PPRA rule 35 (2).

**Muhammad Mazhar Waseem**

Incharge Officer, Procurement & Inventory Control

Allama Iqbal Road Faisalabad, Phone: 041-9201468 & 9201030

**ISSUED TO:**

M/S-----

-----

**TENDER NOTICE No. 392 / 2017****SUPPLY OF EQUIPMENTS FOR DEPARTMENT OF PHARMACEUTICS, GCUF.**

| Sr. No. | Description                                                                            | Specifications                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Qty.   | Unit                  | Total  |
|---------|----------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|-----------------------|--------|
|         |                                                                                        | As Detailed Below or Equivalent                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |        | Price Including Taxes | Amount |
| 1       | pH Meter Digital Bench Model, Model Inolab PH 7110/Set WTW                             | Microprocessor Controlled with parallel Temperature indication, PH Range -2.0 to 20.0 $\pm 0.1$ pH, PH Resolution 0.005pH, MV Range $\pm 1200.0$ mV, Accuracy mV $\pm 0.3$ mv, Automatic Temperature Compensation, Temperature Range -5 to +10.0°C, Temperature accuracy $\pm 0.1$ °C with two/three point Calibration System, Battery operated as well as operated with 220 Volts Complete with accessories                                                                                                                                                                                                                             | 01 No. |                       |        |
| 2       | Magnetic Stirrer with Ceramic Hotplate (Digital), Model AREC.X, With 1000PT probe Velp | Ceramic Top plate, extremely resistant to corrosion, dimension (mm) 180 x 180mm, Temperature range up to 540°C, Stirring volume up to 15 Lit, Electronic speed regulation up to 1300 rpm, Control knob for stirrer and digital temperature, operated on 220 Volts, 800W                                                                                                                                                                                                                                                                                                                                                                  | 01 No. |                       |        |
| 3       | Magnetic Stirrer with Hot Plate Four Places Model AM4, Velp                            | With separate controlled positions of stirrer and heating, Electronic speed control, range up to 1200 rpm (each stirring position)<br><br>Stirring volume (H2O): 5L Per positions temperature up to 370°C                                                                                                                                                                                                                                                                                                                                                                                                                                | 01 No. |                       |        |
| 4       | Vortex Mixer Model Vortex Classic Velp                                                 | Vibrating motion continuously analog dial speed control, Electronic speed regulation 0 – 3000 rpm, Vibration orbit 4.5 mm<br><br>operating mode: touch, continuous , high stability, Operated on 220 Volts                                                                                                                                                                                                                                                                                                                                                                                                                               | 01 No. |                       |        |
| 5       | Shaking Water Bath Memmert, Model WNB14, Memmert                                       | With electronic overtemperature control and a wide range of visual and acoustic signals.<br><br>Temperature range min. 5 °C above ambient up to +95 °C with additional boiling mode (+100 °C). Microprocessor PID-temperature controller with integrated autodiagnostic system with fault indicator, integrated digital timer. Overtemperature Protection (double)<br><br>Interior Stainless Steel Tank & Textured Stainless Steel Casing. Fitted With Gabled Cover<br><br>Operated on 220volts,<br><br>Capacity 14 Lit., interior dimension 350x290x140mm Model WNB14, shaking speed 10-150 stroke/minute Capacity to holds 6 Flasks of | 01 No. |                       |        |

|   |                                                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |           |  |  |
|---|-------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|--|--|
|   |                                                                               | 250ml                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |           |  |  |
| 6 | Homogenizer, Model Silent Crusher M, Heidolph                                 | <p>Digital speed display with superior magnetic drive-less technology, smooth operation as a result of no motor and no mechanical couplings, extremely low noise integrated rpm meter, choice of 10 different tools from 8mm to 18mm Ø</p> <p>Speed range: 5000 to 26000 rpm</p> <p>Dispersing volume From 3 to 1,500 ml</p> <p>Range of viscosity: From 1 to 5000 mPaS</p> <p>Light weight: 1 Kg only</p> <p>Power consumption: 130W</p> <p>Dimension:</p> <p>Drive unit (wxhxd) in mm: 90 x 174 x 90</p> <p>Supply voltage: 100 – 240V, 47 – 63 Hz</p> <p>Steam sterilization: Up to 130°C</p> <p>Hot Air sterilization: Up to 180°C</p> <p>Under pressure or vacuum: 8 bar&amp; 20 mbar</p> <p><b>Accessories:</b></p> <ol style="list-style-type: none"> <li>1. Plate stand P/N 570-17000-00</li> <li>2. Cross sleeve P/N 570-31100-00</li> <li>3. Vessel holding bracket</li> <li>4. Dispersing tool stainless volume range 25-250ml, 9mm dia.</li> </ol> | 01<br>No. |  |  |
| 7 | Digital Electronic Stirrer RZR 2102 Control, Model RZR 2102 Control, Heidolph | <p>2-speed transmission covers a wide speed range at high torque</p> <p>LED for speed range selected</p> <p>Power input: 140 W</p> <p>Power output: 100 W</p> <p>Torque: 400 Ncm max. (peak overload)</p> <p>200 Ncm (continuous)</p> <p>Viscosity range: 100,000 mPa max.</p> <p>Speed range: 12 – 2,000 rpm</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 01<br>No. |  |  |

**Note: Rate should also be quoted on Firm's letter head pad.**

**Details of Call Deposit Receipt (CDR)**

**Signature**\_\_\_\_\_

**No**\_\_\_\_\_ **Amount**\_\_\_\_\_

**Name of Bidder**\_\_\_\_\_

**Bank**\_\_\_\_\_ **Branch**\_\_\_\_\_ **City**\_\_\_\_\_

**CNIC No** \_\_\_\_\_

**Name of the Firm & Address** \_\_\_\_\_ **Ph No**\_\_\_\_\_

**N.T.No.** \_\_\_\_\_ **Sales Tax No.**\_\_\_\_\_

**Issued By:**

**Muhammad Mazhar Waseem**

Incharge Officer, Procurement & Inventory Control

Allama Iqbal Road Faisalabad, Phone: 041-9201468 & 9201030